



ARMORFORM RELEASE 10

EMULSION BASED FORMWORK RELEASE AGENT

FORMWORK RELEASE AGENT

PRODUCT DESCRIPTION

ARMORFORM RELEASE AGENT 10 is a multipurpose form release agent. It is composed of organic chemical that reacts with the free lime content in the concrete and allows for easy de-bonding of the formwork from the concrete. ARMORFORM RELEASE 10 helps to provide a smooth defect free form release and it is suitable for concrete, wood, steel and paper forms.

ADVANTAGES

- Pleasant Smell and ready to use, no additional mixing is required
- Low cost and economical
- Minimizes form stripping time
- Prolong life of form work
- Reduces form cleaning and repairing
- Prevents bonding between poured concrete and the form

APPLICATION AREAS

ARMORFORM RELEASE 10 can be used on various types of forms: wood, steel, fiberglass, aluminum, as well as fiber tubes. **DO NOT USE** on expanded polystyrene (foam), rubber, latex, or latex forms made from SBR or natural rubber. Wood forms should be saturated prior to first use.

COVERAGE

Please note that the coverage rate is dependent on the porosity of the substrate to be treated. The coverage rate given below is for guidance.

Non-porous form surfaces	30 - 35 m ² / litre
Semi-porous form surfaces	25 - 30 m ² / litre
Porous form surfaces	12 - 25 m ² / litre

TECHNICAL DETAILS

Color: Amber Freezing Point: 10° F Staining: None
 VOC Content: 95 g/L

Shelf Life: 12 months

APPLICATION

ARMORFORM RELEASE AGENT 10 should be applied by spraying machine or by roller or brush. It should be applied on form prior to each use. Clean form surfaces thoroughly prior to application. Remove all rust and scale from the forms in accordance with good concrete practices.

STORAGE

Seal the container tightly and store in a cool, well-ventilated place. Avoid damp, sunlight exposure and freezing.



