

ARMORFIX 109

**NON SLIP TILE ADHESIVE FOR CERAMIC TILES
FOR INTERNAL & EXTERNAL TILING**

TILING SOLUTION

PRODUCT DESCRIPTION

ARMORFIX -109 is a high performing, standard setting, cement based tile adhesive. It is suitable for thin and thick bed applications, internal applications. ARMORFIX -109 is polymer modified and has excellent anti-slip properties. It is suitable for the fixing of porcelain, mosaic and ceramic tiles on floor and wall of concrete, concrete block and cement render.

FEATURES

- High adhesive tensile strength
- For internal tiling of walls and floors.
- Polymer modified and therefore provides strong bond for tiles with low porosity
- Easy to mix and apply
- Non sag and anti-slip properties with high initial adhesiveness
- Greater workability due to high pot life

USES

For the installation of floor and wall, ceramic tiles, mosaic, internal applications

SURFACE PREPARATION

The substrate must be fully cured and well prepared, it must be sound, clean, structurally stable, free from dirt, loose particles, efflorescence, chemicals and other contaminants, in order to ensure proper bonding. Standard practice requires at least seven weeks before tiling on concrete and two weeks before tiling on screed.

APPLICATION INSTRUCTION

Pour ARMORFIX-109 into a clean plastic or metal bucket containing clean water, pour adequate quantity of ARMORFIX-109 that can be used within the pot life of 4 hours. 20kg of ARMORFIX -109 requires approximately 4 litres of water. Stir with a mixing device or by hand. Let the mixture rest for 10-15 minutes and restart briefly before application. No further water should be added after mixing.

APPLICATION AND INSTALLATION

Spread ARMORFIX -109 tile adhesive mortar evenly over 1m² area at a time using a notched trowel. Fix tiles immediately within the open time of 20 – 40 minutes. Please be sure that all areas are covered with ARMORFIX -109.

GROUTING

Grouting should be done 24 hours after tiling, for SWIMMING pool leave at least 3 days before grouting and at least one week before filling.

COVERAGE

For thin solid bed application (3mm thickness) 4-5kg of ARMORFIX -109 will cover approximately 1m². Large tiles may need to have the adhesive buttered to the back as well. Ensure that tiles are well bedded into the adhesive. See further information in the technical section below

PACKAGING

20kg bags.

ARMORFIX 109

NON SLIP TILE ADHESIVE FOR CERAMIC TILES FOR INTERNAL & EXTERNAL TILING

TECHNICAL INFORMATION

STANDARD: EN 12004 for C1T

Bed thickness	3 – 6 mm (may be exceeded in small areas only) Coverage (approx.)
Notched trowel	-2.5mm for thin bed 5mm for thick bed
Open time	20 -40 minutes
Correction time	2 hours
Set time	18-24hours
Temperature resistance	-10 to 100°C and frost resistant when set
Water addition	4 litres per 20 kg
Slip resistance	0.5N/mm ²

Note: setting times are quoted at 20°C - 30°C and are temperature and humidity dependent.

CLEANING AND HEALTH

Remove the excess mortar on tools with copious amount of water; if already dry you can remove through mechanical means. Also prolonged contact with skin may occur as it is the case with all cementitious based material, therefore safety gloves and glasses should be used when working.

SHELF LIFE

12 months. Store in a dry place.

LIMITED WARRANTY

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.

Armorsil Manufacturing supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. Armorsil Manufacturing does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to Armorsil Manufacturing in writing within seven working days of being detected.